

ACS ADHESIVE WATERPROOFING MEMBRANE

ACS Adhesive Waterproofing Membrane is a self-adhesive, elastomeric SBS bitumen-based waterproofing membrane, with a high mechanical performance polyethylene film finish on the upper side and easily removable silicone film on the underside.

Dimensions and weight

Nominal thickness (mm)	1.5
Nominal weight (kg/m ²)	1.5
Roll length (m)	20
Roll width (m)	1.00

Pliability (UNE-EN 1109)	Does not break with bending at -20 ⁰ C
Elongation (UNE-EN 12311-1)	Lengthwise 220% Crosswise 200%
Heat resistance (UNE-EN 1110)	Does not drip or sag at 90 ⁰ C
Tensile Strength (UNE-EN 12311-1)	Lengthwise 240 N/5cm Crosswise 240 N/5cm
Static puncturing (UNE-EN 12730 Method B)	Classification L-2 (from 7 – 15 Kg)
Water vapour permeability (BS 3177)	0.33 g/m ² /day
Water vapour resistance (BS 3177)	622 MNs/g
Overlap strength (UNE-EN 12317-1)	240 N
Peel strength (ASTM D-1000) (UNE-EN 12316)	4 N/mm
Thickness (UNE-EN 1849-1)	1.5mm

ACS Adhesive Waterproofing Membrane holds BBA certificate no. 96/3287.

ACS Adhesive Waterproofing Membrane